

Commercial Solutions Division

3M™ Tan Burnish Floor Pad 3400

Product Description

3M™ Tan Burnish Floor Pad 3400 is a floor maintenance burnishing pad made of polyester fibre in a non-woven web construction. The fibres are bonded to the web structure with a durable resin system that permeates the entire pad. Unique design and durable construction make these pads the industry standard for consistent performance and long life.

3M™ Tan Burnish Floor Pad 3400 is designed for burnishing and for use on ultra high speed floor machines operating at 1500 - 3000 rpm.

Uniform coating throughout every 3M™ floor pad reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life. Pads are reversible and will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance. Exacting standards for quality mean thickness uniformity from edge to edge and pad to pad are exceptional, resulting in consistent performance without pad wobble or machine vibration. The precise centre-hole placement and roundness of the pads also contributes to the smooth operation which extends pad life and may help reduce operator fatigue.

Product Line Circular discs and other shapes are available in a variety of common sizes.

Product Characteristics

These are indicative values for unprocessed products.
Contact your 3M representative, if you need more technical information.

Physical & Application	Fibre Type	Polyester
	Weight	20.6 g for 4 x 6 inch (1330 g/m ² nominally)
	Thickness	Nominally 25 mm
	Center Hole	Pre-cut at 85 mm
	Aggressiveness (Schiefer Value)	0
	Colour	Tan
	Marking	3M 3400 TAN BURNISH on each floor pad

Where/When to Use

This product is used on floor machines for burnishing of coated surface floors. For use on finish-coated flooring such as sheet vinyl, vinyl tile, marble, terrazzo or concrete.

Pad Use and Cleaning

Dust mop, damp mop or auto scrub floor as necessary to remove soil prior to burnishing. Dust mop after burnishing to remove residue. Rinse floor and let dry prior to opening to traffic. Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent solution to dissolve caked soil or finish prior to hosing out.

Remarks This bulletin provides technical information only.

Important notice All questions of warranty and liability relating to this product are governed by the terms and conditions of the sale, subject, where applicable, to the prevailing law.
Before using, the user must determine the suitability of the product for its required or intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Additional information Visit the web site of your local subsidiary at www.3M.co.uk/facilities for getting:
- additional instruction bulletins
- a complete product overview about materials 3M is offering



Commercial Solutions Division
Hermeslaan 7
1831 Diegem, Belgium

Responsible for this technical bulletin:

3M Deutschland GmbH
Carl-Schurz-Str. 1
41453 Neuss, Germany

3M is a trademark of 3M Company. All other trademarks are the property of their respective owners.

The use of trademark signs and brand names in this bulletin is based upon US standards. These standards may vary from country to country outside the USA.